

102 – A, Chairman A.Shanmugam Road, SIVAKASI – 616123

Phone: +91-4562-289848/230916 Mobile:9442171616, 7867000916 E-mail: info@arasanaluminium.com Web: www.arasanaluminium.com



Revision No:002 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:005	
1. PRODUCT AND COMPA	ANY IDENTIFICATION		
Product Name	Arasan -Aluminium paste (Mixture of Aluminium powder coated and Paraffin	oil)	
Supplier Name and	The Arasan Aluminium Industries (P) Lt	The Arasan Aluminium Industries (P) Ltd.	
Address	102- A Chairman A. Shunmugam Road, Sivakasi-626 123 Tamil Nadu.India. Phone +914562 230916 Mobile:+919442171616 Email – info@arasanaluminium.com Web – www.arasanaluminium.com		
Trade name	ARASAN - 20 / 80 MO		

2. COMPOSITION /INFORMATION ON INGREDIENTS

Mixtures

Hazardous Components

Chemical Name	CAS No	Classification (REGULATION
	EC number	EC NO 1272/2008)
Aluminium	7429 – 90-5	Flammable Solid
	231-072-3	H 228
Paraffin oil	8042 -47-5	Aspiration Hazard
	232-455-8	H 304

3.HAZARDS IDENTIFICATION

Classification of the Material or Mixture

Classification (REGULATION EC NO 1272 / 2008)

Not a dangerous material or Mixture according to Globally Harmonised System (GHS) **Label elements**

Labelling (REGULATION (EC) No 1272/2008)

Not a dangerous substance or mixture according to the Globally Harmonised System (GHS).



102 – A, Chairman A.Shanmugam Road, SIVAKASI – 616123

Phone: +91-4562-289848/230916 Mobile: 9442171616, 7867000916





Revision No:002	MATERIAL SAFTY DATA SHEET	MSDS No:005
MARCH 2022		
A FIDET AID MEACHIDES		

4. FIRST AID MEASURES

Inhalation: Remove patient to fresh air and consult a physician. Immediately get medical Attention.

Skin contact: wash off with plenty of water

Eye contact: rinse eye with running water, obtain medical attention if symptoms persist

Ingestion: Keep Respiratory tract clear get medical attention.

5. FIRE FIGHTING MEASURES

Suitable extinguishing Agents

dry sand

Unsuitable extinguishing Agents.

- Halogenated fire extinguisher
- Water

6.ACCIDENTAL RELEASE MEASURES

Personal precautions

- Avoid formation of dust clouds
- Do not use vacuum cleaner
- Avoid inhalation of solvent vapors in all circumstances.

Environmental protection

 Do not allow product to enter sewage system or water course (possible reaction releasing hydrogen)



102 – A, Chairman A.Shanmugam Road, SIVAKASI – 616123





Revision No:002	MATERIAL SAFTY DATA SHEET	MSDS No:005
MARCH 2022		

Measures for cleaning/collection spillage:

- O Clean the material using non sparking tools, Avoid formation of dust clouds.
- o If dry, stored in closed drums in dry condition
- o If wet, stored in open topped container in an area with good ventilation and free from Ignition sources.

7. HANDLING AND STORAGE

Handling

- O Avoid source of sparks or other source of ignition
- Protect against static electricity
- Use suitable explosion proof equipment and spark –proof tools
- O Avoid accidental contact with reactive materials- acid or chemicals-oxidiser etc
- Use non sparkling tools

Storage

- Keep the Material in the container Always air tight
- o If the drums are in open condition, volatile Mater will be evaporated and the properties of the Material will be changed.
- o The area should be suitably marked to indicate the presence of an ignitable dust
- Avoid sparks or other source of ignition
- Keep area clean and avoid spillage
- Do not store with reactive materials

8. EXPOSURE CONTROLS/PERSONAL PROTECTION Monitoring procedure

Provide adequate ventilation

Respiratory protection: Use suitable breathing protection if workplace concentration

requires.

Hand protection: Solvent-resistant gloves (butyl-rubber)

Eye protection: Safety glasses.



102 – A, Chairman A.Shanmugam Road, SIVAKASI – 616123

Phone: +91-4562-289848/230916 Mobile:9442171616, 7867000916 E-mail: info@arasanaluminium.com Web: www.arasanaluminium.com



Revision No:002	MATERIAL SAFTY DATA SHEET	MSDS No:005
MARCH 2022		

9. PHYSICAL AND CHEMICAL PROPERITY

Physical state : Solid (Paste)

Color : Silver

Odour : NA

P.H : NA

Boling temperature : 2467°C (Aluminium)

Melting temperature : 660 °C (Aluminium)

Flash Point : NA

Explosive prosperity : No data available

Solubility : insoluble in water

10.STABILITY AND REACTIVITY

Stability

Stable at room temperature

Reactivity

May react with acids or oxidizing agents or halogenated hydrocarbons

11.TOXICOLOGICAL INFORMATION

Acute Toxicity

No data available

Chromic toxicity

Not Harmful

102 – A, Chairman A.Shanmugam Road, SIVAKASI – 616123

Phone: +91-4562-289848/230916 Mobile:9442171616, 7867000916





Revision No:002 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:005
12.ECOLOGICAL INFORMATION	ON	

Ecotoxicity

- Aluminium powder is not ecotoxic
- o Generally not hazardous to water

13. DISPOSAL CONSIDERTIONS

In accordance with national and local regulations.

Waste

Dispose of in line with regional or national regulations. Avoid product entering water coarse/sewer system

14.TRANSPORT INFORMATION

Not a Hazardous material as defined by transport regulation

15.REGULATORY INFORMATION

Safety

Safety phrase -7/8, 24/25, 43 S-7/8-keep container tightly closed and dry

S-24/25 avoid contact with skin and eyes

S-43-in case of fire use sand –NEVER use water

Full text of H-Statements

H228 Flammable solid.

H304 May be fatal if swallowed and enters airways.

16. OTHER INFORMATION

The information on this data sheet represents our current data to proper use in handling of this product under normal conditions, and only as a safety guideline, not as a product specification. No warranty, either expressed or implied, is hereby made. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.