



The Arasan Aluminium Industries (P) Ltd.

Revision No:006 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:002
1. PRODUCT AND COMPANY IDENTIFICATION		
Product Name Chemical Symbol	Aluminium paste (Mixture of Aluminium powder coated and Mineral Turpentine) AL MTO	
CAS No	7429-90-5	64742-81-0
EINECS No	231-072-3	265-184-9
Supplier Name and Address	The Arasan Aluminium Industries (P) Ltd. 102 A Chaiman A.Shanmugam Road,Sivakasi-626 123 Tamil Nadu.India. Phone -04562 230916, 94421 71616 787000916, 17 Email – info@arasanaluminium.com Web – www.arasanaluminium.com	
Trade name	30 NL	
2. COMPOSITION /INFORMATION ON INGREDIENTS		
NAME	CAS No	UN NO
Aluminium	7429-90-5	1309
MTO	64742-81-0	1223
3.HAZARDS DENTIFICATION		
Human health	- No data available	
Environment	- No data available	
Physical		
If suspended in air (dust cloud), fine powder can be ignited in the presence of an ignition source and cloud pose an explosion risk in a confirmed environment		
Chemical		
Prolonged contact with water may results in reaction releasing flammable hydrogen gas -Fire and explosion risk		
Will react with oxidizing agent or acids or alkalis, causing heat and hydrogen release- Fire and explosion risk		
Can react violently with halogenated hydrocarbons Explosion risk		



Revision No:006 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:002
4. FIRST AID MEASURES		
Inhalation: No known health risk – treat as nuisance dust		
Skin contact: wash off with plenty of water		
Eye contact: rinse eye with running water, obtain medical attention if symptoms persist		
Ingestion: rinse out mouth and then drink copious amount of water. Do not induce vomiting. Obtain medical attention.		
5. FIRE FIGHTING MEASURES		
Suitable extinguishing Agents		
<ul style="list-style-type: none">➤ Gently smother burning material with dry sand➤ Use foam or carbon -di-oxide cylinder		
Unsuitable extinguishing Agents.		
<ul style="list-style-type: none">➤ Halogenated fire extinguisher➤ Water		
Special hazards caused by the substance, its products of combustion or resulting gases		
<ul style="list-style-type: none">➤ Dust can combine with air to form an explosive mixture➤ Contact with water releases flammable gas (hydrogen)		
6.ACCIDENTAL RELEASE MEASURES		
Personal precautions		
<ul style="list-style-type: none">➤ Avoid formation of dust clouds➤ Keep away ignition sources➤ Avoid inhalation of solvent vapours in all circumstances.		
Environmental protection		
Do not allow product to enter sewage system or water course (possible reaction releasing hydrogen)		



Revision No:006 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:002
Measures for cleaning/collection spillage: <ul style="list-style-type: none">➤ Clean the material using non sparking tools (eg.Natural fiber brown).Avoid formation of dust clouds.➤ If dry, stored in closed drums in dry condition➤ If wet, stored in open topped container in an area with good ventilation and free from ignition sources.		
7. HANDLING AND STORAGE		
Handling <ul style="list-style-type: none">➤ Avoid generation of dust clouds➤ Avoid source of sparks or other source of ignition➤ Protect against static electricity➤ Use suitable explosion proof equipment and spark –proof tools➤ Keep work area clean➤ Avoid accidental contact with reactive materials- acid or chemicals-oxidiser etc➤ Use non sparking tools Storage <ul style="list-style-type: none">➤ Keep the Material in the container Always air tight➤ If the drums are in open condition, volatile Mater will be evaporated and the properties of the Material will be changed.➤ The area should be suitably marked to indicate the presence of an ignitable dust➤ Avoid sparks or other source of ignition➤ Keep area clean and avoid spillage➤ Do not store with reactive materials		
8. EXPOSURE CONTROLS/PERSONAL PROTECTION		
Exposure limits		
Work place Long-term exposure (TLV) – 8 hrs TWA – 10 mg/m ³		
Exposure controls Respiratory protection A suitable face mask is recommended if regular exposure is un avowable .if work place concentration requires the use of respiratory protection – use filter types		
Eye protection Not normally required. Irritation may occurs as with any dust entering the eye – wash out immediately if it occurs.		
Skin contact Wash of with plenty of water – remove the contaminated clothing		



Revision No:006 MARCH 2022	MATERIAL SAFTY DATA SHEET	MSDS No:002
9. PHYSICAL AND CHEMICAL PROPERITY		
Physical state : Semi -Solid		
Form : Paste		
Color : Silver white		
Odour : Solvent smell		
P.H : NA		
Boling temperature : 2467 °C (Aluminium) 145 °C-205 °C (MTO)		
Melting temperature : 660 °C (Aluminium)		
Flash Point : 35 °C		
Auto Flammability : 252 °C (MTO)		
Explosive prosperity : No data available		
Minimum Ignition tempt : Cloud 610 °C Layer 320 °C		
Oxidizing properties : Will react exothermically if mixed with a strong oxidizing Substance and liquid		
Real density : 1.4-1.6gm/cm ³		
Solubility : insoluble in water		
10.STABILITY AND REACTIVITY		
Stability Stable at room temperature		
Reactivity May react with acids or oxidizing agents or halogenated hydrocarbons Prolonged contact with water can cause a reaction releasing hydrogen gas.		
11.TOXICOLOGICAL INFORMATION		
Acute Toxicity No data available		
Chromic toxicity No chromic effects known		
TLV – 10mg/m ³ (General dust limit)		



Revision No:006 MARCH 2022	MATERIAL SAFETY DATA SHEET	MSDS No:002
12.ECOLOGICAL INFORMATION		
Mobility /Degradability ➤ Will convert to Aluminium oxide (alumina) during prolonged contact with water		
Ecotoxicity ➤ Aluminium powder is not ecotoxic ➤ Generally not hazardous to water		
13. DISPOSAL CONSIDERTIONS		
Waste Dispose of in line with regional or national regulations. Avoid product entering water coarse/sewer system		
14.TRANSPORT INFORMATION		
Transport over land ADR/RID class	- 4.1	Correct technical name: aluminium Flammable solid organic N.O.S 9Aluminium paste) UN No.1325 Ems.No.F-G.S-G
Transport oversea IMDG class	- 4.1	
Transport over ICAO/IATA class	n - 4.1	
Packing group	- II	
15.REGULATORY INFORMATION		
Label : UN classification -4.1 Flammable solids		
Risks		
Risk Phrase -10,15	R-10- Flammable	
	R-15-contect with water librates extremely flammable gas	
Safety		
Safety phrase -7/8,43.6	S-7/8-keep container tightly closed and dry	
	S-43.6-in case of fire use sand –NEVER use water	
16. OTHER INFORMATION		
The information on this data sheet represents our current data to proper use in handling of this product under normal conditions, and only as a safety guideline, not as a product specification. No warranty, either expressed or implied, is hereby made. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.		